

# SLCV-608C

Camera for video vigilance with interchangeable optics.  
Interior use.



### TECHNICAL INFORMATION

- **POWER SUPPLY**  
Voltage nominal ..... 12vdc.  
( Power supply source for 230vac  
50Hz included).
- **CONSUMPTION**  
Nominal consumption ..... 180mA.

- **OTHER INFORMATION**  
Type of sensor: Color Sharp 1/4 " CCD .  
Video system: PAL.  
Resolution: 500 (H) X 582 (V).  
Horizontal resolution: 420 Lines TV.  
Relation of signal / noise: 48db.  
Minimum lighting: 1,0 Lux.  
Lens: 6mm.  
Video output: 1.0Vp-p 75Ohm - BNC .  
Dimensions (length x width x height): 120mm x  
55mm x 55mm.  
Construction: Aluminum.  
Working temperature -10°C ... +50°C.

CAUTION: It is supplied without optic.

## OBJECTIVES (OPTIONAL) FOR CAMERA SLCV-608C



### SLCV F02 1/3" CS

Cod.: 12079  
Optic 2mm. 1/3" CS



### SLCV F04 1/3" CS

Cod.: 11999  
Optic 4mm. 1/3" CS



### SLCV F1.2 1/3" CS

Cod.: 12416  
Optic 6mm. 1/3" CS



### SLCV F04 1/3" CS

Cod.: 12417  
Optic 8mm. 1/3" CS



### SLCV F04 1/3" CS

Cod.: 12418  
Optic 16mm. 1/3" CS



### SLCV-CS 8mm Autoiris

Cod.: 12421  
Optic 8mm. 1/3" CS Autoiris



### SLCV-CS 2.8-12mm Autoiris

Cod.: 12225  
Optic 2.8 - 12mm. 1/3" CS Autoiris manual zoom.  
Opening F1.4.